



KAPCI
COATINGS

Technical Data Sheet

Issue date January 2024

for professional use only

Kapci 100 Underbody

Product description

Kapci 100 is a product based on cyclo rubber designed to protect car underbody from stone chipping and corrosion. It can also be applied over the body floor and other metal parts. Kapci 100 gives anticorrosion properties, excellent adhesion and chemical resistance.


Substrates

Kapci 100 undercoat should be applied over rust free and degreased bare metal. For longer resistance to corrosion, it is recommended to apply an anticorrosive primer prior to overcoating with Kapci 100.

Application



Thoroughly degrease the surface. For steel use Kapci 606 Degreaser for metal.



Mixing ratio by weight:

Add 20% Kapci 525 NC thinner and mix well.



Use underbody (UB) gun

Nozzle: 6-8mm; Pressure:4-5 bar

Apply 1-2 coats.



Air dry at 20°C:

Dry to handle: 1-2h

Hard dry: 24h

Health and Safety

1. For full Health and Safety information refer to the Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and suitable protective equipment must be worn while using these products.
4. Good ventilation must be provided in the working environment.

IMPORTANT NOTE: These TDS are for information purposes only without any obligation as we do not have control over the quality and conditions of the surface or application.